

JM Ceiling Pro Lucent

Technical specification



JM Ceiling Pro Lucent FR				
Article Артикул		03-2113-3100	03-2113-4100	03-2113-5100
Basic material Основной материал		100 % polyester (acrylic polymer coated) 100% полиэстер (акриловое полимерное покрытие)		
Weave Тип плетения		woven fabric ткань		
Width Ширина		310 cm / 122†	410 cm / 161†	510 cm / 201†
Weight approx. Вес	EN ISO 2286-2	210 g/m² / 6,2 oz/yd²		
Thickness approx. Толщина	EN ISO 2286-3	0,38 mm / 0,015†		
Light fastness Светостойкость	EN ISO 105-B02	7		
Dimensional change (temperature) Изменение размеров (температура)	110°C, 2 min	warp: ≤ 0,5 % weft: ≤ 0,5 %		
Dimensional change (moisture) Изменение размеров (влажность)	DIN 53892-2	warp: ≤ 0,5 % weft: ≤ 0,5 %		
Tensile strength Предел прочности	EN ISO 1421	warp: ≥ 800 N / 5 cm weft: ≥ 500 N / 5 cm		
Tear strength Прочность на разрыв	EN ISO 1875-3	warp: ≥ 30 N weft: ≥ 40 N		
Fire classification Пожарная классификация	EN 13501-1	B-s1, d0		
Light transmittance Коэффициент пропускания света	EN 410 : 30 %	56 %		
Degree of whiteness approx. Степень белизны	according to Berger	approx. 80		
Printability Возможность фотопечати		yes (UV, latex, solvent) да (УФ, латекс, сольвент)		
Care instruction Инструкция по уходу		spongeable моющийся		
Manufacturing guidance Руководство по производству		to cut with cold knife резать макетным ножом		
Roll length approx. Длина рулона		50 m / 55 yd		

The information provided in this document do not exempt processors from carrying out own tests and trials as further handling and processing may show significant effects on our products. Application, utilization and processing of products are beyond our control and are therefore the sole responsibility of the processors.

All specifications are based on average values and may deviate within the standard tolerance limits. Subject to technical modifications.

Product certificates and guarantees

Sustainable building certificates

All JM fabrics certified according to SCS Advantage™ Gold can contribute to credits in sustainable building certifications, such as DGNB, BREEAM and LEED.

JM Ceiling Pro Lucent



PVC-free - без ПВХ



water resistant - водостойкий



tear-resistant - прочный на разрыв



good crease recovery -
хорошее восстановление складок



textile appearance -
текстильный внешний вид



easy to clean - легко очистить



translucent - полупрозрачный



flame retardant - огнестойкий

JM Ceiling Pro Lucent

digitally printed

